

External Label Rewinder



Efficient and User-friendly

Postek R120 External Label Rewinder features auto-adaptive torque technology to automatically adjust rewinding speed to the printer's printing speed.

It is the perfect complement to the exceptional performance of any barcode label printer with label width of 2.5 cm to 12 cm, and its maximum rewinding speed reaches up to 10 ips.



Safe and Durable

Postek A Series Rotary cutter is designed as a value-added accessory for special applications to Postek barcode label printers.

All metal blade and rotary cutter design assures its trust-worthy proficiency. It is safe to use with the patent structural design.

POSTEK Ribbon



Original and Affordable

Postek original high quality ribbon provides an affordable choice to ensure perfect printouts while effectively protecting the printhead to extend its life.



SPECIFICATIONS

n120

External Label Rewinder

Mode	R120			
Max Rewinding Speed	10 ips (254 mm/s)			
Label Width	0.98″ – 4.72″ (25 mm – 120 mm)			
Max Rewinding OD	8″ (203 mm)			
Max Rewinding ID	3″ (76.2 mm)			
Dimension	W 8.66" × D 10.31" × H 9.13"			
Weight	4.2 kgs			

A150/A300 Rotary cutter

Mode	A150	A300				
Applicable Label	Uncontinuous adhe	Uncontinuous adhesive labels (cut on liner only)				
	Unadhesive media,	Unadhesive media, e.g. wash label, card paper				
Max Cutting Width	4.72″ (120 mm)					
Max Media Thickness	0.005″ (0.15 mm)	0.011″ (0.30 mm)				
Applicable Models	C168 Series, G Seri	es, TX Series, TXr Series				

ACCESSORIES

	V6	Q8 Series	C168 Series	G Series	TX Series	TXr Series	
External Label Rewinder							
Rotary Cutter							
Guillotine Cutter							
Manual Cutter							
Peeler Kit							
External Media Stand		(Standard)					
Media Guide Adaptor							
Centronics Parallel					(Stan	dard) 🔳 (Standa	







POSTEK ELECTRONICS CO., LTD.

Wisdom Plaza, Block B, Tower 2, 18th Floor Qiaoxiang Road, Nanshan District, Shen Zhen, Guang Dong, China

T +86-755-83240988 F +86-755-83202898

WWW.POSTEK.COM.CN